Amendment to the Claims:

This listing of claims will replace all prior versions and listings of claims in the application:

1. (Currently Amended) A polymer composite consisting of at least one, optionally hydrogenated, nitrile rubber polymer having a Mooney viscosity (ML 1+4 @ 100°C) in the range of from 50-30 and a polydispersity index of less than 2.7, at least one filler and optionally at least one cross-linking agent.

wherein the optionally hydrogenated, nitrile rubber polymer is prepared by reacting a nitrile polymer in the presence of one ore more compounds of the general formulas I, II, III or IV

$$X$$
 M
 C
 R

Formula I


wherein:

M is Os or Ru.

R and R¹ are, independently, hydrogen or a hydrocarbon selected from the group consisting of C₂-C₂₀ alkenyl, C₂-C₂₀ alkynyl, C₁-C₂₀ alkyl, aryl, C₁-C₂₀ carboxylate, C₁-C₂₀ alkoxy, C₂-C₂₀ alkenyloxy, C₂-C₂₀ alkylyloxy, aryloxy, C₂-C₂₀ alkoxycarbonyl, C₁-C₂₀ alkylthio, C₁-C₂₀ alkylsulfonyl and C₁-C₂₀ alkylsulfinyl,

X and X1 are independently any anionic ligand, and

L and L¹ are independently any neutral ligand, such as phosphines, amines, thioethers or imidazolidinylidene (which are especially preferred) or any neutral carbene, optionally, L and L¹ can be linked to one another to from a bidentate neutral ligand;



Formula II

wherein;

M1 is Os or Ru;

R² and R³ are, independently, hydrogen or a hydrocarbon selected from the group consisting of C₂-C₂₀ alkenyl, C₂-C₂₀ alkynyl, C₁-C₂₀ alkyl, aryl, C₁-C₂₀ carboxylate, C₁-C₂₀ alkoxy, C₂-C₂₀ alkenyloxy, C₂-C₂₀ alkylyloxy, aryloxy, C₂-C₂₀ alkoxycarbonyl, C₁-C₂₀ alkylthio, C₁-C₂₀ alkylsulfonyl and C₁-C₂₀ alkylsulfinyl,

X2 is a anionic ligand, and

L² is a neutral π-bonded ligand, independent of whether they are mono- or polycyclic,

L³ is a ligand selected from the group consisting of phosphines, sulfonated phosphines, fluorinated phosphines, functionalized phosphines bearing up to three aminoalkyl-, ammoniumalkyl-, alkoxylcarbonylalkyl-, hydrocycarbonylalkyl-, phosphinites, phosphinites, phosphinites, phosphinites, phosphinites, arsines, stibenes, ethers, amines, amides, imines, sulfoxides, thioethers and pyridines, Y- is a non-coordinating anion, n is an integer in the range of from 0 to 5:

$$OR^{7}_{2}$$
 M^{2}
 R^{4}
 R^{5}

Formula III

wherein

M2 is Mo or W.

R⁴ and R⁵ are, independently, hydrogen or a hydrocarbon selected from the group consisting of C₂-C₂₀ alkenyl, C₂-C₂₀ alkynyl, C₁-C₂₀ alkyl,

$$X = C = C$$

$$X^{1} = C = C$$

$$R^{1}$$

Formula IV

arvi, C_1 - C_{20} carboxylate, C_1 - C_{20} alkoxy, C_2 - C_{20} alkenvloxy, C_2 - C_{20} alkynvloxy, aryloxy, C_2 - C_{20} alkoxycarbonyl, C_1 - C_{20} alkylsulfonyl and C_1 - C_{20} alkylsulfinyl,

R⁶ and R⁷ are independently selected from any unsubstituted or halo-substituted alkyl, aryl, aralkyl groups or silicon-containing analogs thereof, wherein:

M is Os or Ru,

R and R¹ are independently selected from the group consisting of hydrogen, substituted or unsubstituted alkyl, and substituted or unsubstituted alkyl.

PO-7959

X and X¹ are independently any anionic ligand, and

L and L¹ are independently any neutral ligand, such as phosphines,

amines, thioethers or imidazolidinylidene (which are especially

preferred) or any neutral carbene, optionally, L and L¹ can be linked
to one another to from a bidentate neutral ligand.

- 2. (Previously Presented) The polymer composite according to Claim 1 wherein the Mooney viscosity (ML 1+4 @ 100°C) is in the range of from 45-30.
- 3. (Previously Presented) The polymer composite according to Claim 1 wherein the Mooney viscosity (ML 1+4 @ 100°C) is in the range of from 40-30.
- 4. (Previously Presented) The polymer composite according to Claim 1, wherein the polymer composite comprises a peroxide or sulfur curing system.
- 5. (Previously Presented) A process for preparing the polymer composite according Claim 1 comprising mixing at least one, optionally hydrogenated, nitrile rubber polymer having a Mooney viscosity (ML 1+4 @ 100°C) in the range of from 50-30 and a polydispersity index of less than 2.7, at least one filler and optionally at least one cross-linking agent.
- 6. (Previously Presented) A process for the manufacture of a shaped article comprising the step of injection molding a polymer composite comprising at least one, optionally hydrogenated, nitrile rubber polymer having a Mooney viscosity (ML 1+4 @ 100°C) in the range of from 50-30 and a polydispersity index of less than 2.7, at least one filler and at least one cross-linking agent.
- 7. (Previously Presented) The process according to Claim 6, wherein the shaped article is a seal, a hose, a bearing pad, a stator, a well head seal, a valve plate, a cable sheathing, a wheel roller, a belt, in place gaskets or a pipe seal.

 PO-7959

 -5-